

TYGRIS TECHNICAL DATA SHEET

Industrial Maintenance Aerosols

Graffiti Remover

CODE: **R251**

Targeted action for quick and easy renovation

A powerful solvent and wetting agent based formulation making the removal of unwanted markings quick and effective, with minimal effect on the substrate. Will remove graffiti from plastics, wood, metal, glass, and most painted surfaces



Benefits:

- Use on a wide range of surfaces including many plastics
- Wetting agents make for effective penetration
- Methylene Chloride free
- Easy to apply
- Rapid penetration
- Fast drying

Technical Data:

Appearance: Clear liquid
Odour: Solvent
Contents: Blend of 2-methoxy-1-methyl ethyl acetate, acetone, n-butyl acetate, methylal, 1,3 dioxolane and fatty alcohol ethoxylate with butane/propane propellant

Storage: Below 50°C
Flash Point: <0°C
Temperature range: For use at ambient temperatures
Relative Density: 0.87

Solubility:
Pack Sizes: 12 x 400ml cans

Directions for Use: Shake can well before use and spray onto surface from a distance of 20 to 25 cm. Allow a few minutes to wet and penetrate the graffiti and wipe off. Can also be rinsed off with water.

Check compatibility on plastics. Do not use on hot surfaces where evaporation may occur before penetration.