## **TYGRIS TECHNICAL DATA SHEET**

Industrial Maintenance Aerosols

## **Graffiti Remover - Viscous**

## CODE: **R252**

Remove graffiti fast with this thickened formula for use on vertical surfaces

This thickened powerful graffiti remover is effective in the removal of paint graffiti, ink and felt tip, particularly on vertical surfaces or areas where the slow evaporation aids in penetration for capable erasure of unwanted marks.

Benefits:

Thixotropic to aid in clinging to vertical surfaces Water washable Slow drying for better penetration Removes paint, biro, felt tip pin Easily applied Non-chlorinated Also effective in the removal of old gaskets

Technical Data:

Appearance:	Clear foaming spray
Odour:	Solvent
Contents:	Blend of acetone, hydrocarbon wax, thickeners and odourless kerosene in a dimethyl ether propellant
Storage:	Below 50°C
Flash Point:	<0°C
Temperature range:	For use at ambient temperatures
Relative density:	0.95
Solubility:	Soluble in water
Pack Sizes:	12 x 400ml cans
Directions for Use:	Spray directly onto affected area from 20-25cm, allow a short time for product to penetrate, and wipe away to remove graffiti. Rinse as necessary. <b>Test a small unobtrusive area on coated or</b> <b>painted surfaces first to ensure compatibility.</b> <b>Not suitable for use on uPVC or polycarbonate.</b>

