

SAFETY DATA SHEET

according to Regulation (EU) 2020/878

Page 1/10

Insette Scent of Jasmine Airfreshener

Revision 2

Revision date 2025-05-20

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Insette Scent of Jasmine Airfreshener

Other means of identification

/ UFI

UFI: TP00-D06P-A002-CAD1

1.3. Details of the supplier of the safety data sheet

Company LEC (Lpool) Ltd

Address LEC House

Alfred Street

Wavertree

Liverpool L15 2JJ

sales@insette.com

Web www.insette.com

Telephone +44 (0) 151 734 1411

Email sales@insette.com

Email address of the competent person

1.4. Emergency telephone number

Emergency telephone number +44 (0) 151 734 1411

Company LEC (Lpool) Ltd

9.00 am - 5.00 pm GMT Mon - Fri

NPIS

NHS 111 (England) T: 111

NHS 24 (Scotland) T: 111

NHS Direct (Wales) T: 111 or 0845 46 47

 $Northern\ \underline{Ireland\ -\ contact\ your\ GP.\ Out\ -of\ -hours:\ www.gpout\ of\ hours.hscni.net}$

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC

on - EC

Aerosols 1: H222;

2.1.2. Classification - EC

H229 - Pressurised container: May burst if heated.

2.2. Label elements

1272/2008

1272/2008

Hazard pictograms



Signal Word

Hazard Statement

Danger

Aerosols 1: H222 - Extremely flammable aerosol.

Revision date 2025-05-20

2.2. Label elements

Precautionary Statement:	P102 - Keep out of reach of children.			
Prevention	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No			
	smoking.			
	P211 - Do not spray on an open flame or other ignition source.			
	P251 - Do not pierce or burn, even after use.			
Precautionary Statement:	P403+P235 - Store in a well-ventilated place. Keep cool.			
Storage	P410+P412 - Protect from sunlight. Do no expose to temperatures exceeding 50°C/ 122°F.			
Precautionary Statement:	P501 - Dispose of contents/container to in accordance with local and national regulations.			
Disposal				
2.3. Other hazards				
	_			

Other hazards	This product does not contain any known or suspected endocrine disruptors. This mixture does not
	contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH No.	Conc. (%w/w)	Classification
Petroleum gases, liquified.		68476-85-7	270-704-2		20 - 30%	Flam. Gas 1: H220; Aerosols
(Liquefied petroleum gas)						1: H222; Liquified gas: H280;
Jasmin RP3117 AF-22 15671					0.5 - 1%	Skin Sens. 1: H317; Eye Irrit.
						2: H319; Aquatic Chronic 2:
						H411;
Sodium Nitrite 99%	007-010-00-4	7632-00-0	231-555-9		0 - 0.5%	Ox. Sol. 3: H272; Acute Tox.
						3: H301; Eye Irrit. 2: H319;
						Aquatic Acute 1: H400;

Further information

Full text of Hazard Statements listed in this Section is provided in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air. If the person is breathing, but unconscious, place them in the recovery position. Obtain medical assistance immediately. Treat symptomatically. Administer oxygen if necessary.
Eye contact	Treat frostbite with lukewarm water. Get immediate medical advice/attention. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing. Cover the cold burns with sterile dressings. Do not apply ointments or powders.
Skin contact	Remove all contaminated clothes and footwear immediately unless stuck to skin. Contaminated clothing may be a fire hazard and should be soaked with water before being removed. Treat frostbite with lukewarm water. Get immediate medical advice/attention. Cover the cold burns with sterile dressings. Do not apply ointments or powders.
Ingestion	Rinse mouth thoroughly. DO NOT INDUCE VOMITING.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	May cause irritation to respiratory system. High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea. Continued exposure may result in unconsciousness and/or death.
Eye contact	May cause irritation to eyes. Cold burns (frostbite) will result from eye contact with liquid.
Skin contact	May cause irritation to skin. Cold burns (frostbite) will result from skin contact with liquid.
Ingestion	May cause irritation to mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

 Revision
 2

 Revision date
 2025-05-20

		Revision date	2025-05-2
4.3. Indication of any immediate medical a	uttention and special treatment needed		
Inhalation	Seek medical attention. Treat symptomatically. Administer oxygen if necessary.		
Eye contact	Seek medical attention.		
Skin contact			
Skill Collact	Seek medical attention if irritation or symptoms persist. Treat frostbite with lukewarm water. Get immediate medical advice/attention.		
Ingestion	Seek medical attention if irritation or symptoms persist.		
General information			
Jeneral Information			
	If you feel unwell, seek medical advice (show the label where possible).		
Further information			
	Contact with liquefied gas can cause frostbite due to rapid evaporative cooling.		
SECTION 5: Firefighting measures			
5.1. Extinguishing media			
	Use extinguishing media appropriate to the surrounding fire conditions.		
5.2. Special hazards arising from the subs			
	Flammable liquid and vapour. Heat will increase pressure in sealed containers. Pressurised		
	containers are liable to explode violently when subjected to high temperatures. Cool fire exposed containers with waterspray. Burning produces obnoxious and irritating fumes.		
5.2 Advice for firefighters	ositamos mai natospia). Baning protesto sanamata ana mitamig tantos		
i.3. Advice for firefighters			
	Wear protective gloves/protective clothing/eye protection/face protection. The vapour is heavier		
	than air, spreads along the ground and distant ignition is possible. Any firefighting products should		
	be contained using appropriate methods. Attempt to prevent the gas from entering low lying areas e.g. cellars, pits, drains, sewers or confined spaces. Attempt to prevent the gas from entering		
	watercourses e.g. rivers, sewers. Check wind direction and attempt to disperse the vapours or to		
	direct their flow (e.g. by using water curtains or fog sprays) to a safer location e.g. area free from		
	ignition sources.		
OFOTION C: A seldental release mass			
SECTION 6: Accidental release meas			
3.1 Personal precautions, protective equi-			
	pment and emergency procedures		
Goottal procedurorio, proceduro equi	Evacuate personnel to a safe area. Contact emergency response personnel. Test atmosphere for		
sicona piocadione, piococino equi			
sicona piocadione, piococaro equi	Evacuate personnel to a safe area. Contact emergency response personnel. Test atmosphere for		
sicona piocadione, piocosi o equi	Evacuate personnel to a safe area. Contact emergency response personnel. Test atmosphere for flammable gas concentrations to ensure safe working conditions before personnel are allowed to		
The second procedure, process of equi	Evacuate personnel to a safe area. Contact emergency response personnel. Test atmosphere for flammable gas concentrations to ensure safe working conditions before personnel are allowed to enter the area. Vapour may travel considerable distance to source of ignition and flash back. Wear		
	Evacuate personnel to a safe area. Contact emergency response personnel. Test atmosphere for flammable gas concentrations to ensure safe working conditions before personnel are allowed to enter the area. Vapour may travel considerable distance to source of ignition and flash back. Wear suitable protective clothing and eye/face protection. Ensure adequate ventilation of the working		
	Evacuate personnel to a safe area. Contact emergency response personnel. Test atmosphere for flammable gas concentrations to ensure safe working conditions before personnel are allowed to enter the area. Vapour may travel considerable distance to source of ignition and flash back. Wear suitable protective clothing and eye/face protection. Ensure adequate ventilation of the working		
	Evacuate personnel to a safe area. Contact emergency response personnel. Test atmosphere for flammable gas concentrations to ensure safe working conditions before personnel are allowed to enter the area. Vapour may travel considerable distance to source of ignition and flash back. Wear suitable protective clothing and eye/face protection. Ensure adequate ventilation of the working area. Avoid prolonged or repeated exposure.		
	Evacuate personnel to a safe area. Contact emergency response personnel. Test atmosphere for flammable gas concentrations to ensure safe working conditions before personnel are allowed to enter the area. Vapour may travel considerable distance to source of ignition and flash back. Wear suitable protective clothing and eye/face protection. Ensure adequate ventilation of the working area. Avoid prolonged or repeated exposure. Advise local authorities if large spills cannot be contained. Attempt to prevent the gas from		
6.2. Environmental precautions	Evacuate personnel to a safe area. Contact emergency response personnel. Test atmosphere for flammable gas concentrations to ensure safe working conditions before personnel are allowed to enter the area. Vapour may travel considerable distance to source of ignition and flash back. Wear suitable protective clothing and eye/face protection. Ensure adequate ventilation of the working area. Avoid prolonged or repeated exposure. Advise local authorities if large spills cannot be contained. Attempt to prevent the gas from entering watercourses e.g. rivers, sewers. Do not allow product to enter drains. Do not let product contaminate subsoil.		
6.2. Environmental precautions	Evacuate personnel to a safe area. Contact emergency response personnel. Test atmosphere for flammable gas concentrations to ensure safe working conditions before personnel are allowed to enter the area. Vapour may travel considerable distance to source of ignition and flash back. Wear suitable protective clothing and eye/face protection. Ensure adequate ventilation of the working area. Avoid prolonged or repeated exposure. Advise local authorities if large spills cannot be contained. Attempt to prevent the gas from entering watercourses e.g. rivers, sewers. Do not allow product to enter drains. Do not let product contaminate subsoil.		
6.2. Environmental precautions	Evacuate personnel to a safe area. Contact emergency response personnel. Test atmosphere for flammable gas concentrations to ensure safe working conditions before personnel are allowed to enter the area. Vapour may travel considerable distance to source of ignition and flash back. Wear suitable protective clothing and eye/face protection. Ensure adequate ventilation of the working area. Avoid prolonged or repeated exposure. Advise local authorities if large spills cannot be contained. Attempt to prevent the gas from entering watercourses e.g. rivers, sewers. Do not allow product to enter drains. Do not let product contaminate subsoil.		
6.2. Environmental precautions	Evacuate personnel to a safe area. Contact emergency response personnel. Test atmosphere for flammable gas concentrations to ensure safe working conditions before personnel are allowed to enter the area. Vapour may travel considerable distance to source of ignition and flash back. Wear suitable protective clothing and eye/face protection. Ensure adequate ventilation of the working area. Avoid prolonged or repeated exposure. Advise local authorities if large spills cannot be contained. Attempt to prevent the gas from entering watercourses e.g. rivers, sewers. Do not allow product to enter drains. Do not let product contaminate subsoil. It and cleaning up Avoid any spark creation. Do not use tools which may produce sparks. Absorb with inert,		
5.2. Environmental precautions 5.3. Methods and material for containment	Evacuate personnel to a safe area. Contact emergency response personnel. Test atmosphere for flammable gas concentrations to ensure safe working conditions before personnel are allowed to enter the area. Vapour may travel considerable distance to source of ignition and flash back. Wear suitable protective clothing and eye/face protection. Ensure adequate ventilation of the working area. Avoid prolonged or repeated exposure. Advise local authorities if large spills cannot be contained. Attempt to prevent the gas from entering watercourses e.g. rivers, sewers. Do not allow product to enter drains. Do not let product contaminate subsoil. It and cleaning up Avoid any spark creation. Do not use tools which may produce sparks. Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Contact a		
5.2. Environmental precautions 6.3. Methods and material for containment	Evacuate personnel to a safe area. Contact emergency response personnel. Test atmosphere for flammable gas concentrations to ensure safe working conditions before personnel are allowed to enter the area. Vapour may travel considerable distance to source of ignition and flash back. Wear suitable protective clothing and eye/face protection. Ensure adequate ventilation of the working area. Avoid prolonged or repeated exposure. Advise local authorities if large spills cannot be contained. Attempt to prevent the gas from entering watercourses e.g. rivers, sewers. Do not allow product to enter drains. Do not let product contaminate subsoil. It and cleaning up Avoid any spark creation. Do not use tools which may produce sparks. Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Contact a		
6.2. Environmental precautions 6.3. Methods and material for containment 6.4. Reference to other sections SECTION 7: Handling and storage	Evacuate personnel to a safe area. Contact emergency response personnel. Test atmosphere for flammable gas concentrations to ensure safe working conditions before personnel are allowed to enter the area. Vapour may travel considerable distance to source of ignition and flash back. Wear suitable protective clothing and eye/face protection. Ensure adequate ventilation of the working area. Avoid prolonged or repeated exposure. Advise local authorities if large spills cannot be contained. Attempt to prevent the gas from entering watercourses e.g. rivers, sewers. Do not allow product to enter drains. Do not let product contaminate subsoil. It and cleaning up Avoid any spark creation. Do not use tools which may produce sparks. Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Contact a licensed waste disposal company.		
6.2. Environmental precautions 6.3. Methods and material for containment 6.4. Reference to other sections	Evacuate personnel to a safe area. Contact emergency response personnel. Test atmosphere for flammable gas concentrations to ensure safe working conditions before personnel are allowed to enter the area. Vapour may travel considerable distance to source of ignition and flash back. Wear suitable protective clothing and eye/face protection. Ensure adequate ventilation of the working area. Avoid prolonged or repeated exposure. Advise local authorities if large spills cannot be contained. Attempt to prevent the gas from entering watercourses e.g. rivers, sewers. Do not allow product to enter drains. Do not let product contaminate subsoil. It and cleaning up Avoid any spark creation. Do not use tools which may produce sparks. Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Contact a licensed waste disposal company.		
6.2. Environmental precautions 6.3. Methods and material for containment 6.4. Reference to other sections SECTION 7: Handling and storage	Evacuate personnel to a safe area. Contact emergency response personnel. Test atmosphere for flammable gas concentrations to ensure safe working conditions before personnel are allowed to enter the area. Vapour may travel considerable distance to source of ignition and flash back. Wear suitable protective clothing and eye/face protection. Ensure adequate ventilation of the working area. Avoid prolonged or repeated exposure. Advise local authorities if large spills cannot be contained. Attempt to prevent the gas from entering watercourses e.g. rivers, sewers. Do not allow product to enter drains. Do not let product contaminate subsoil. It and cleaning up Avoid any spark creation. Do not use tools which may produce sparks. Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Contact a licensed waste disposal company.		
6.2. Environmental precautions 6.3. Methods and material for containment 6.4. Reference to other sections SECTION 7: Handling and storage	Evacuate personnel to a safe area. Contact emergency response personnel. Test atmosphere for flammable gas concentrations to ensure safe working conditions before personnel are allowed to enter the area. Vapour may travel considerable distance to source of ignition and flash back. Wear suitable protective clothing and eye/face protection. Ensure adequate ventilation of the working area. Avoid prolonged or repeated exposure. Advise local authorities if large spills cannot be contained. Attempt to prevent the gas from entering watercourses e.g. rivers, sewers. Do not allow product to enter drains. Do not let product contaminate subsoil. It and cleaning up Avoid any spark creation. Do not use tools which may produce sparks. Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Contact a licensed waste disposal company. See Section(s) 2, 8, 13 for further information.		

 Revision
 2

 Revision date
 2025-05-20

	handling and discharge may cause fire. Ensure electrical continuity by earthing all equipment. Eliminate all sources of ignition.
7.2. Conditions for safe storage, i	including any incompatibilities
	Store in a well-ventilated area, away from ignition sources and other sources of heat. Store in correctly labelled containers. Keep at temperature not exceeding 25°C.
Suitable packaging	Keep only in original container.
7.3. Specific end use(s)	
	See section 1.2. Relevant identified uses of the substance or mixture and uses advised against for further information. Please refer to Product Information Sheet & Label before using this product.

8.1. Control parameters

Occupational exposure controls.

8.1.1. Exposure Limit Values

			=
Petroleum gases, liquified.	WEL 8-hr limit ppm: 1000	WEL 8-hr limit mg/m3: 1750	
(Liquefied petroleum gas)			
	WEL 15 min limit ppm: 1250	WEL 15 min limit mg/m3: 2180	
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -	
	inhalable dust:	inhalable dust:	
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -	
	respirable dust:	respirable dust:	
Sodium Nitrite 99%	WEL 8-hr limit ppm:	WEL 8-hr limit mg/m3: 2	
	WEL 15 min limit ppm:	WEL 15 min limit mg/m3:	
	WEL 8-hr limit mg/m3 total	WEL 15 min limit mg/m3 total	
	inhalable dust:	inhalable dust:	
	WEL 8-hr limit mg/m3 total	WEL 15 min limit mg/m3 total	
	respirable dust:	respirable dust:	

8.2. Exposure controls

8.2.1. Appropriate	Ensure adequate ventilation of the working area. Provide engineering controls to ensure exposure
engineering controls	levels are controlled.
8.2.2. Individual protection	Wear suitable protective clothing. PPE must meet applicable European or national standards.
measures	
Eye / face protection	Wear eye/face protection. If there is a risk of splashing or spray wear chemical splash goggles
	(gas-tight mono goggles), face shield with chin guard or a hybrid of safety glasses and googles
	-approved to EN-166.
Skin protection -	Wear suitable gloves. If contact with product spray is possible or anticipated use gloves against
Handprotection	cold (EN-511) e.g. polar grip gloves.
Skin protection - Other	Wear suitable protective clothing.
Respiratory protection	Avoid breathing vapour or spray mist. Wear suitable respiratory equipment when necessary.
	Suitable half mask respirator with filter P2 (EN 143).
Thermal hazards	Extremely flammable liquid and vapour. Do not use or store near heat or open flame.
8.2.3. Environmental	Avoid release to the environment.
exposure controls	
Occupational exposure	Ensure adequate ventilation of the working area. Exposure above the recommended occupational
controls	exposure limit (OEL) may cause adverse health effects.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Revision 2

Revision date 2025-05-20

9.1. Information on basic physical and chemical properties

Appearance	Aerosol
Colour	White
Odour	Characteristic
Oxidising properties	No data available
Odour threshold	No data available
pH	8.5 - 10
Melting point	No data available
Freezing Point	No data available
Initial boiling point	No data available
Flash point	60 °C
Evaporation rate	No data available
Flammability (solid, gas)	Extremely flammable gas
Upper Explosive Limit	9 %
Lower Explosive Limit	2 %
Vapour pressure	No data available
Relative Vapour Density	No data available
Density / Relative Density	0.927 (H2O = 1 @ 20 °C)
Fat Solubility	No data available
Partition coefficient (P)	No data available
Autoignition temperature	No data available
Decomposition temperature	> 442 °C
Viscosity	No data available
Solubility	No data available
<u> </u>	

9.2. Other information

Conductivity	No data available
Surface tension	No data available
Gas group	No data available
Benzene Content	Not applicable.
Lead content	Not applicable.
VOC (Volatile organic compounds)	≥ 10 %
compounds)	

9.2.1. Information with regard to physical hazard class	es
---	----

9.2.2. Other safety characteristics					

SECTION 10: Stability and reactivity			
10.1. Reactivity			
	Hazardous reactions are not expected under normal transport or storage conditions.		
10.2. Chemical stability			
	This product is chemically stable under recommended conditions of storage, use and temperature.		
10.3. Possibility of hazardous reactions			
	Extremely flammable liquid and vapour. Contact with combustible material may cause fire.		
10.4. Conditions to avoid			
	Creation of flammable atmospheres. Potential sources of ignition. Heat, sparks and open flames.		
10.5. Incompatible materials			
	Oxidising agents. Combustible materials.		

Revision 2

Revision date 2025-05-20

		Revision date	2025-05-20		
10.6. Hazardous decomposition products					
	Hazardous decomposition products are not expected during normal storage. Burning produces obnoxious and irritating fumes.				
SECTION 11: Toxicological information	n				
11.1 Information on hazard classes					
Acute toxicity	No data is available on this product.				
Skin corrosion/irritation	May cause irritation to skin. Contact with liquid product will cause cold burns and frostbite to the skin.				
Serious eye damage/irritation	May cause eye irritation. Cold burns (frostbite) will result from eye contact with liquid.				
Respiratory or skin sensitisation	No sensitizaton effects reported.				
Germ cell mutagenicity	No mutagenic effects reported.				
Carcinogenicity	No carcinogenic effects reported.				
Reproductive toxicity	No teratogenic effects reported.				
STOT-single exposure	STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure .				
STOT-repeated exposure	No data is available on this product.				
Aspiration hazard	No data is available on this product.				
Repeated or prolonged	Avoid prolonged or repeated exposure.				
exposure	<u> </u>				
11.2 Information on other hazards					
	No data is available on this product.				
SECTION 12: Ecological information					
12.2. Persistence and degradability					
	Readily biodegradable.				
12.3. Bioaccumulative potential					
	This product does not bioaccumulate.				
12.4. Mobility in soil					
	No data is available on this product.				
12.5. Results of PBT and vPvB assessment					
	This product does not contain any substances classified as PBT or vPvB.				
12.6 Endocrine disrupting properties					
	This product does not contain any known or suspected endocrine disruptors.				
12.7 Other adverse effects					
	Harmful to aquatic life with long lasting effects.				
SECTION 13: Disposal considerations					
General information					
	Contact a licensed waste disposal company.				
Disposal methods					
	Dispose of in compliance with all local and national regulations.				
Disposal of packaging	•				
Fruit as informed	Do NOT reuse empty containers. Empty containers can be sent for disposal or recycling. Do not pierce or burn, even after use. Empty containers represent a fire hazard as they will contain flammable product residues and vapour.				
Further information					

Revision

		Revision date	2025-05-20	
Further information				
	For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used.			
SECTION 14: Transport information				
Hazard pictograms				
	2			
14.1. UN number				
	UN1950			
14.2. UN proper shipping name	•			
	AEROSOLS			
14.3. Transport hazard class(es)	•			
ADR/RID	2			
Subsidiary risk	see SP63			
IMDG	2			
Subsidiary risk	see SP63			
IATA	2			
Subsidiary risk	see SP63			
14.4. Packing group				
Packing group	-			
14.5. Environmental hazards				
Environmental hazards	No			
Marine pollutant	No			
14.6. Special precautions for user				
	Ensure that persons transporting the product know what to do in the event of an accident or			
	spillage.			
14.7 Maritime Transport in bulk according t	o IMO instruments			
	No data is available on this product.			
ADR/RID				
Hazard ID	-			
Tunnel Category	(D)			
IMDG				
EmS Code	F-D S-U			
IATA				
Packing Instruction (Cargo)	203			
Maximum quantity	150 kg			
Packing Instruction (Passenger)	203			
(Passenger) Maximum quantity	75 kg			
Further information	1 ~			
	Classified as dangerous goods for carriage under road/rail/sea/air regulations. This product is			
	packed in accordance with the Limited Quantity Provisions of CDG, ADR and IMDG. These			

Revision 2
Revision date 2025-05-20

Further information

provisions allow transport of aerosols of less than 1 litre packed in cartons of less than 30kg gross weight to be exempt from control providing that they are labelled in accordance with the Limited Quantities requirements of these regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

Regulation EU 2016/425 on personal protective equipment.

Framework Directive 89/391/EEC on the introduction of measures to encourage improvements in the safety and health of workers at work – as amended.

Directive 89/656/EEC on the minimum health and safety requirements for the use by workers of personal protective equipment at the workplace (3 individual directive) – as amended.

Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work - as amended.

Directive 1999/92/EC on minimum requirements for improving the safety and health protection of workers potentially at risk from explosive atmospheres – as amended.

Directive 2008/98/EC on waste - as amended.

Directive 2012/18/EU on the control of major accident hazards involving dangerous substances.

Directive 2008/68/EC on inland transport of dangerous goods – as amended.

Aerosol Dispensers Regulations 2009.

The Aerosol Dispensers (Amendment) Regulations 2018.

15.2. Chemical safety assessment

A Chemical Safety Assessment has not been carried out

SECTION 16: Other information

Other information

Revision

This document differs from the previous version in the following areas:

9 - 9.1. Information on basic physical and chemical properties (Flash point).

Acronyms

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways:

ADR - Agreement concerning the International Carriage of Dangerous Goods by Road;

AIIC - Australian Inventory of Industrial Chemicals;

ASTM -American Society for the Testing of Materials; bw - Body weight;

CMR - Carcinogen, Mutagen or Reproductive Toxicant;

DIN - Standard of the German Institute for Standardisation;

DSL - Domestic Substances List (Canada);

ECx - Concentration associated with x% response;

 ${\sf ELx} \hbox{ -Loading rate associated with $x\%$ response};$

EmS -Emergency Schedule;

ENCS - Existing and New Chemical Substances (Japan);

 $\label{eq:encoder} \text{ErCx -} \text{Concentration associated with } x\% \text{ growth rate response};$

Revision 2
Revision date 2025-05-20

Other information

GHS - Globally Harmonized System;

GLP - Good Laboratory Practice;

IARC - International Agency for Research on Cancer;

IATA - International Air Transport Association;

IBC - International Code for the Construction and Equipment of Ships carrying Dangerous

Chemicals in Bulk;

IC50 - Half maximal inhibitory concentration;

ICAO - International Civil Aviation Organization;

IECSC - Inventory of Existing Chemical Substances in China;

IMDG - International Maritime Dangerous Goods;

IMO - International Maritime Organization;

ISHL - Industrial Safety and Health Law (Japan);

ISO - International Organisation for Standardization;

KECI - Korea Existing Chemicals Inventory;

LC50 - Lethal Concentration to 50 % of a test population;

LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose);

MARPOL - International Convention for the Prevention of Pollution from Ships;

N.O.S. -Not Otherwise Specified;

NO(A)EC - No Observed (Adverse) Effect Concentration;

NO(A)EL - No Observed (Adverse) Effect Level;

NOELR - No Observable Effect Loading Rate;

NZIoC - New Zealand Inventory of Chemicals;

OECD - Organization for Economic Co-operation and Development;

OPPTS - Office of Chemical Safety and Pollution Prevention;

PBT - Persistent, Bioaccumulative and Toxic substance;

PICCS - Philippines Inventory of Chemicals and Chemical Substances;

 $\hbox{(Q)SAR - (Quantitative) Structure Activity Relationship;}\\$

REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council

 $concerning \ the \ Registration, \ Evaluation, \ Authorisation \ and \ Restriction \ of \ Chemicals;$

 $\label{eq:RID-Regulations} \textbf{RID-Regulations concerning the International Carriage of Dangerous Goods by Rail;}$

SADT - Self-Accelerating Decomposition Temperature;

SDS -Safety Data Sheet;

TCSI - Taiwan Chemical Substance Inventory;

TECI - Thailand Existing Chemicals Inventory;

TSCA - Toxic Substances Control Act (United States);

UN - United Nations;

UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods;

vPvB - Very Persistent and Very Bioaccumulative. Aquatic Acute = Hazardous to the aquatic

environment (acute)

Aquatic Chronic = Hazardous to the aquatic environment (chronic)

Asp. Tox. = Aspiration hazard

Eye Dam. = Serious eye damage

Carc. = Carcinogenicity

Eye Irrit. = Eye irritation

Flam. Liq. = Flammable liquid

Press. Gas (Liq.) = Gas under pressure: Liquefied gas

Skin Irrit. = Skin irritation

Skin Sens. = Skin sensitisation

STOT RE = Specific target organ toxicity-repeated exposure

STOT SE = Specific target organ toxicity-single exposure

Text of Hazard Statements in Section 3

Flam. Gas 1: H220 - Extremely flammable gas.

Aerosols 1: H222 - Extremely flammable aerosol.

Liquified gas: H280 - Contains gas under pressure; may explode if heated

Skin Sens. 1: H317 - May cause an allergic skin reaction.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Ox. Sol. 3: H272 - May intensify fire; oxidiser.

2

Revision

Insette Scent of Jasmine Airfreshener

Other information

Acute Tox. 3: H301 - Toxic if swallowed.
Aquatic Acute 1: H400 - Very toxic to aquatic life.

Turther information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.